

5DS01B

Switching Diode



Features

[Go to Home Page](#)

- High – speed

Item	Characteristics
Wafer size	5inch
Chip size	240*240um

Maximum Ratings @25degC

Item	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V _{RSM}	100	V
Repetitive Peak Reverse Voltage	V _{RRM}	75	V
Repetitive Peak Forward Current	I _{FRM}	500	mA
Continuous Forward Current	I _O	150	mA
Non-Repetitive Peak Forward Current @t=1us	I _{FSM}	2	A
Power Dissipation	P _D	500	mW
Junction Temperature	T _j	175	degC
Storage Temperature	T _{stg}	-65to+175	degC

Electrical Characteristics @25degC

Item	Symbol	Min	Max	Unit	Test Condition
Forward Voltage	V _F		1.05	V	I _F =100mA
Breakdown Voltage	V _B	100		V	I _R =100uA
Reverse Current	I _R		25	nA	V _R =20V
Junction Capacitance	C _T		4	pF	V _R =0V, f=1MHz
Reverse Recovery Time	t _{rr}		4	nsec	I _F =I _R =10mA R _L =100Ω, i _{rr} =1mA

Probing Spec @25degC

Symbol	Min	Max	Unit	Test Condition
V _F		1.05	V	I _F =100mA
V _B	105		V	I _R =100uA
I _{R1}		25	nA	V _R =30V
I _{R2}		2	uA	V _R =85V
C _T		4	pF	V _R =0V, f=1MHz
t _{rr}		4	nsec	I _F =I _R =10mA R _L =100Ω, i _{rr} =1mA

Note Equivalent type : BAW62

SheetNo. F07026A

Rev. 0