

SPEC SHEET (FOR REFERENCE)	SHEET No. G05036A	Rev. 2	Page. 1 of 1
----------------------------	--------------------------	---------------	---------------------

TYPE6PT1606P3T * *

CHIP SIZE	0.36 * 0.36mm
WAFER SIZE	6 inch

Maximum Ratings (Ta=25°C)

Characteristics	Symbol	Ratings	Unit
Drain-Source voltage	V _{DSS}	-50	V
Gate-Source voltage	V _{GSS}	±20	V

PROBING SPEC (Ta=25°C)

No	MODE	LIMIT			UNIT	CONDITIONS
		MIN.	Typ	MAX.		
1	IGSS			+10	uA	VGS=+-20V, VDS=0V
2	IDSS			-1	uA	VDS=-52V, VGS=0V
3	BVDSS	-52			V	ID=-100uA, VGS=0V
4	V _{th}	-1		-2	V	ID=-250uA, VGS=VDS
5	RDS(on)1		5.5	10	Ω	VGS=-5.0V, ID=-100mA
6	RDS(on)2		4.5	8	Ω	VGS=-10.0V, ID=-100mA
7	VSD			1.4	V	IS=115mA, VGS=0V
8	Yfs	100			mS	VDS=-10V, ID=-100mA

* ESD Protected:1000v