

1A 60V(0.82mm)

[Go to Home Page](#)

Chip Information

Chip Size	0.82 x 0.82mm
Pad Size	0.68 x 0.68mm
Chip Quantity	16276 pcs/wafer
Scribe Line Width	60um
Passivation	SIN
Wafer Size	5 inch
Top Metallization	Al-Ni-Au (For Solder)

Chip Thickness/Back Metal : See below "Ordering Information"

MAXIMUM RATINGS

Parameter	Symbol	Limit	Unit	Note
Repetitive Peak Reverse Voltage	VRRM	60	V	
Non-Repetitive Peak Reverse Voltage	VRSM		V	
Maximum DC Blocking Voltage	VR		V	
Average Forward Rectified Current	IF(AV)	1	A	
Peak Forward Surge Current	IFSM	40	A	8.3ms Single Half Sine-Wave
Storage and Operating Temperature Range	Tj,TSTG	-65 to +125	degC	

ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Spec Limit	Probe Spec	Typical	Unit	Test Condition
Maximum Forward Voltage	VF1	0.670		0.600	V	IF=1A Ta=25degC
	VF2				V	
	VF3				V	
	VF4				V	
	VF5				V	
Maximum DC Reverse Current	IR1	0.2	0.1	0.005	mA	VR=62V Ta=25degC
	IR2				mA	
	IR3				mA	
	IR4				mA	
Reverse Breakdown Voltage	BV	62	65	72	V	IR=0.3mA
Junction Capacitance	Cj			35	pF	V=4V f=1MHz
Reverse Recovery Time	trr				nS	

Ordering Information

Chip Type	Chip Thickness	Back metal
XMB512	250 +/- 20um	Ti-Ni-Au (For Solder)

Note:

Designed For SR106,SB160